

Model

View

Features

BPM-170LS

BPM-200LS

BPM-240AS



Front



Rear

- 1366x768 Resolution with high contrast 900:1(17")
- 2xHD/SD SDI inputs
- 1xDVI Input, 1xHDMI Input(W/HDCP)
- Analog Composite/Component/S-Video/RGB Input
- 1:1 Pixel Mapping Mode for SD/HD
- Audio Disembeder&Speakers
- Optional 19" Rack Mount Kit available(also VESA Competible)
- Supports BON color calibration utility for proper color alignment
- Waveform/Vector Scope(SDI)
- UMD
- Closed Caption(CEA608/708/Trascoded)
- Embedded Audio Level Meter(16CH)
- Waveform/Vector same time display simultaneously, Vector Scope (75%, 100% mode display), Grayscale Adjustments using color depth 16 step waveform and vector scope
- V-Chip Data display for SD-SDI, Analog
- PaP function (Picture and Picture)
 - ◆ Comparing 2 video with each other on Freezing mode
- H/V FLIP Mode

Specifications

HD/SD-SDI Input	2EA, HD/SD Serial Digital, 1.485G/270M, BNC Jack				
Analog Input	3EA, Composite, YC (S-Video), YPbPr, RGB, BNC Jack				
PC-RGB(DVI) Input	1EA, DVI + Analog Jack (with gender) (24Pin + 5Pin)				
DVI Input	1EA, DVI-I, 24pin, Female				
HDMI Input	1EA, HDMI (with HDCP v.1.1), 19pin Female				
SDI Output	1EA, BNC, SDI-Selected Active Loop Output				
Analog Loop Output	3EA, 75Ω, BNC Jack (Option)				
Analog Input	Composite (CVBS), YC(S-Video), Component (Y/Pb/Pr), Component (R/G/B), DVI-RGB, Sync Level				
Input Signal Format	2K Format, SMPTE 274M, SMPTE 296M, SMPTE 260M, SMPTE 259M, 125M, ITU R-BT.656, YPbPr/RGB, HDMI Digital, DVI Digital, PC-RGB(DVI) Mode				
Audio Input	1EA, L/R, Stereo pin jack, SDI Audio Input (Embedded HD/SD-SDI Audio)				
Audio Output	1EA, L/R, Stereo pin jack, Speaker Output (2EA, 2W+2W), Ear-phone Output (1EA, L/R Stereo, 3.5mm Stereo pin jack)				
Audio Output Signal	Input Line & De-embedded Audio, 1~16CH				
I/O Port	GPI Remote (1EA, Remote, RJ-45P Jack, GPI-7 Port), Serial Update (2EA, RJ-11P Jack, RS-422, Serial interface)				
LCD	Size	17"	20"	24"	
	Resolution	1366 x 768	1366 x 768	1920 x 1200	
	Pixel Pitch	0.091 x 0.273 mm	0.108 x 0.324mm	0.270 mm	
	Color	16.7M	16.7M	16.7M	
	Viewing Angle (deg)	R/L:178, U/D:178	R/L:178, U/D:178	R/L:178, U/D:178	
	Luminance of White	350 cd/m ²	410 cd/m ²	400 cd/m ²	
	Contrast	900 : 1	600:1	800:1	
	Display Area (H x V)	372.91 x 209.66 mm	443.6 x 249.4mm	518.4 x 324 mm	
Power Requirements	DC 12V/5.5A, AC		AC 100~230V, 50Hz/60Hz		
Dimension (mm), Detail Drawing as rear page	420.5 x 310 x 98.4		479 x 328 x 96.3		553.8 x 408 x 99.8
Option Accessories	Rack Mount,Wall Mount,V-Mount,Hood,Carrying Case(17")/Rack Mount,Wall Mount,Carrying Case(20"-24")/Stand,Carrying Case,Wall Mount(32"-47")				