


DVB Master™ 2i/2o

**DVB-ASI Receiver/Transmitter Card –
Two Input Ports Feature Hardware Based
Automatic Packet Size Detection, PID
Filtering, and Packet Arrival Timestamping.
Two Output Ports Feature Enhanced Rate
Control and Jitter Management.**



Features

- Two transmitter channels and two receiver channels on the same PCI card
- Aggregate data rate to 400 Mbits/second
- Multiple boards can be used for more inputs and outputs
- Bandwidth can be divided as required between ports
- Cable Equalization on receive channels
- Uses highly efficient Bus Master Link List DMA for data transform (saving CPU resources)
- Provides an interface for Layer-0 & Layer-1 of the DVB-ASI standard
- Uses the proven Cypress™ HotLink® interface chip
- External clock input via NTSC or PAL black burst signal (available from on-board header)
- External clock reference input (available from on-board header)
- Drivers for Windows® 7 32 and 64 bit, Server 2003, Server 2008, Windows® 2000, Windows® XP, and Linux®
- Windows® XP/Server 2003/Server 2008/Linux® API
- DirectShow® filter
- Advanced Receiver Capabilities –
 - Synchronizes incoming packets to byte boundaries
 - Automatic 188 and 204 packet size detection
 - Interrupt on in/out of sync
 - Software selectable option to strip 16 bytes from 204 byte packets
 - Unlimited PID filtering (any number of PIDs may be selected)
- Advanced Transmitter Capabilities –
 - Enhanced transmit rate “Fine Tuning” control to <2.8ppm granularity
 - Software selectable option to add sixteen – 0x00 bytes to 188 byte packets
 - External transmit clock inputs (black burst or external reference clocks)

Applications

- DVB VoD (Video on Demand) Servers
- Cable TV
- Broadcast TV

Overview

Worldwide the television industry is currently in the process of changing from analog to digital technology. MPEG-2 has now been universally adopted as the main standard for video compression. Since MPEG-2 must be decoded at the same rate it was encoded, an information layer needs to be added to the MPEG in order to transmit it to end users. Standards have been created by industry to provide for the methodology of packetizing MPEG-2 streams and adding encoding information in tables via data packets to the video packets. The DVB standard has been approved by the European Community and other industry and government groups as the standard to accommodate the need for satellite and terrestrial originated digital television. This product complies with the DVB-ASI specifications as defined in ETSI TR 101 891 and provides for the ability of computers to capture, process, and transmit DVB-ASI compliant streams.

DVB-ASI defines a method of digitally transmitting MPEG-2 Transport Streams at 270 mbps and is designed to be transmitted via QPSK modulation via a satellite-based router to the home receiver. It is usually composed of many standard definition 4-6 Mbps streams multiplexed together with associated audio streams in various languages into a Multi Program Transport Stream. This is the standard that is usually used to feed most brands of DVB Modulators. Our DVB Master 2i/2o device can be used to provide multiple inputs and outputs to source video servers or test equipment that is compatible with the DVB-ASI standard.



Computer Modules, Inc.

11409 West Bernardo Court

San Diego, CA 92127


Tel: 858-613-1818 Fax: 858-613-1815

www.dveo.com

Specifications

Dimensions	
Width:	4.20 inches (10.67 cm)
Length:	6.875 inches (17.46 cm)
Thickness:	0.58 inches (1.47 cm)
Typical Weight	5.2 oz (147 g)
Input/Output Connectors	75 Ohm BNC
External Clock Input	Black burst NTSC/PAL (header)
Data Input/Output	DVB-ASI Coaxial, 2 Kbps to 213 Mbps data rate (400 Mbps aggregate across 4 channels)
Typical Power	850 mA @ 5 V
Operating Temperature	0 to 55° C
Operating Humidity	To 90%, Non-condensing
Status LED Indicators	Rx with Carrier Detect, Tx
Receive/Transmit FIFO Size	4 KB (Rx), 8 KB (Tx) each channel
Bus Interface	PCI 2.2; 5V/3.3V, 33/66 MHz, 32 bit
Driver Support	Windows® 7 – 32 and 64 bit, Windows XP, Windows Server 2003, Windows Server 2008, and Linux®
DVB Standards	CENELEC EN50083-9: 1998 – Cable distribution systems for television, sound and interactive services – Part 9: Interfaces for CATV/SMATV headends and similar professional equipment for DVB/MPEG-2 transport streams.

Block Diagram



Ordering Information

DVB Master™ 2i/2o (Model 125)

© 2011 Computer Modules, Inc. DVEO and DVB Master are trademarks of Computer Modules, Inc. DVB is a registered trademark of the DVB Project. All other trademarks and registered trademarks are the properties of their respective owners. All rights reserved. Specifications are subject to change without notice.

Receiver Capabilities

Receive Packet Synchronization – The DVB Master 2i/2o receiver checks the incoming transport stream for packet sync, and synchronizes on it. Once synchronized, the packets are stored on packet boundaries in memory. This makes further processing of the transport stream much easier for the host processor.

Packet Arrival Timestamping – Under software control, each packet is timestamped with an arrival time generated by an internal timer/counter.

Null Packet Insertion – Under software control but performed by hardware, "null packets" are automatically inserted into the bit stream to replace filtered PIDs.

Automatic Packet Size Detection – The DVB Master 2i/2o automatically detects packet size and indicates the current size in a status register. If packet size changes suddenly, it will lose synchronization, then resynchronize on the new packet size and indicate the new packet size in the status register.

In/Out of Sync Interrupt – An interrupt is generated whenever synchronization is lost or recovered. Interrupts indicate that the status of the stream should be checked.

16 byte Strip – The 16 byte Stripping function removes the extra 16 Reed-Solomon encoded bytes from the 204 byte packets to create 188-byte packets.

PID Filtering – Select any number of PIDs from the total of over 8,000 possible PIDs to be filtered from the stream. The DVB Master 2i/2o receiver channels block all PIDs that are not selected.

Transmitter Capabilities

Transmitter Fine Tuning – In some applications, such as reading files from a disk, it may be desirable to use stuffing to control the transmission rate of the stream to match the rate required by the Program Clock Reference (PCR) of a Transport Stream. Because of this, we have developed the Fine Tuning (FT) feature. Fine Tuning is accomplished by first setting the standard IP and IB to select a rate as close to the desired rate as possible. Then the FT parameter can be set to bring the rate within 2.5ppm of the target. This method of rate control works with small Tx buffers and gives minimum latency.

Software Controlled Transmit Clock Selection – The transmit clock options include the Black Burst clock, External Clocks and Internal Clock. The black burst input accepts a black burst signal for either NTSC or PAL video and is available as an on-board header.

Null Packet Insertion – Under software control but performed by hardware, "null packets" are automatically inserted into the bit stream.

PCR Pacing – Firmware support is available for releasing PCR packets at the correct PCR time. This method ensures that the transmit rate and PCR timing are the same as the original input stream.

Reed-Solomon Conversion – The software can be set to have hardware add 16 bytes filled with zeros to 188-byte packets to create a 204-byte packet stream.

DVEO
Broadcast Division

Computer Modules, Inc.

11409 West Bernardo Court

San Diego, CA 92127

Tel: 858-613-1818 Fax: 858-613-1815

www.dveo.com